

Specifications

C-Models

The laminators of the C-series are pure cold laminators. A warming-up of the upper roller is not possible.

Model	<i>RoilLam 120C</i>	<i>RoilLam 140C</i>	<i>RoilLam 160C</i>
Working width / Roller width	120 cm / 130 cm	140 cm / 150 cm	160 cm / 170 cm
Width / depth / height	170 / 68 / 121cm	190 / 68 / 121 cm	210 / 68 / 121 cm
Height of front worktable	87,5 cm	87,5 cm	87,5 cm
Weight	168 kg	188 kg	218 kg
Max. board thickness	25 mm	25 mm	25 mm
Diameter of rollers	112 mm	112 mm	130 mm
Max. speed	3,5 m/min	3,5 m/min	4 m/min
Voltage	230V / 0,07 KW	230V / 0,07 KW	230V / 0,07 KW
Adjustment of height	central	central	central
Finger protection	yes	yes	yes
Foot switch	yes	yes	yes
Unroll and upwind axis (at the top)	yes	yes	yes
Unroll axis (at the bottom)	yes	yes	yes
Quick gripping cones	yes	yes	yes
Forward and reverse action	yes	yes	yes
Speed adjustable	yes	yes	yes
CE-certificate	yes	yes	yes

W-Models

The upper roller of the models *RoilLam 80W*, *RoilLam 120W*, *RoilLam 140W* and *RoilLam 160W* is equipped with a thermoelement what makes it possible to heat the silicone roller to approx. 30°C-60°C.

Model	<i>RoilLam 80W</i>	<i>RoilLam 120W</i>	<i>RoilLam 140W</i>	<i>RoilLam 160W</i>
Thermoelement	30°C-60°C	30°C-60°C	30°C-60°C	30°C-60°C
Working width / Roller width	80 cm / 88 cm	120 cm / 130 cm	140 cm / 150 cm	160 cm / 170 cm
Width / depth / height	110 / 50 / 108 cm	170 / 68 / 121 cm	190 / 68 / 121 cm	210 / 68 / 121 cm
Height of front worktable	87 cm	87,5 cm	87,5 cm	87,5 cm
Weight	50 kg	168 kg	188 kg	218 kg
Max. board thickness	12 mm	25 mm	25 mm	25 mm
Diameter of rollers	65 mm	112 mm	112 mm	130 mm
Max. speed	1,5 m/min	3,5 m/min	3,5 m/min	4 m/min
Voltage	230V / 0,8 KW	230V / 0,9 KW	230V / 1,0 KW	230V / 1,3 KW
Adjustment of height	central	central	central	central
Finger protection	yes	yes	yes	yes
Silicone rollers	yes	yes	yes	yes
Foot switch	yes	yes	yes	yes
Unroll and upwind axis (at the top)	yes	yes	yes	yes
Unroll axis (at the bottom)	yes	yes	yes	yes
Quick gripping cones	yes	yes	yes	yes
Forward and reverse action	yes	yes	yes	yes
Speed adjustable	-	yes	yes	yes
CE-certificate	yes	yes	yes	yes

Inspected and accredited by TÜV Rheinland



Leopold
 PROFESSIONAL IMAGING
 Div of LEOPOLD CAMERAS LTD
 Colex House, 57 Lancaster Road,
 New Barnet, Herts EN4 8AS
 Telephone: 020-8441 4310
 Facsimile: 020-8449 0317
www.leopold.co.uk

